



Resilient Wireless Sensor Networks

A thesis submitted in fulfilment of the
requirements for the award of the degree

Doctor of Philosophy

from

UNIVERSITY OF TECHNOLOGY, SYDNEY
Faculty of Engineering and Information Technology

by

Ali Rafiei

Bachelor Science of Engineering, 2004
Master Science of Engineering, 2007
Shiraz University

SYDNEY, AUSTRALIA
2017

Statement of Authorship/Originality

I certify that the work in this thesis has not been previously submitted for a degree nor has it been submitted as a part of the requirements for other degree except as fully acknowledged within the text.

I also certify that this thesis has been written by me. Any help that I have received in my research and in the preparation of the thesis itself has been fully acknowledged. In addition, I certify that all information sources and literature used are quoted in the thesis.

© Copyright 2017, Ali Rafiei



Abstract

With the increase in wireless sensor networks' (WSN) applications as the result of enhancements in sensors' size, battery-life and mobility, sensor nodes have become one of the most ubiquitous and relied-upon electrical appliances in recent years. In harsh and hostile environments, in the absence of centralised supervision, the effects of faults, damages and unbalanced node deployments should be taken into account as they may disturb the operation and quality of service of networks. Coverage holes (CHs) due to the correlated failures and unbalanced deployment of nodes should be considered seriously in a timely manner; otherwise, cascaded failures on the rest of the proximate sensor nodes can jeopardise networks' integrity. Although different distributed topology control (TC) schemes have been devised to address the challenges of node failures and their dynamic behaviours, little work has been directed towards recovering CHs and/or alleviating their undesirable effects especially in Large Scale CHs (LSCH). Thus, devising CH recovery strategies for the swift detection, notification, repair and avoidance of damage events are important to increase the lifetime and resiliency of WSNs and to improve the efficacy and reliability of error-prone and energy-restricted nodes for many applications. In this research, the concepts of resiliency, fault management, network holes, CHs, TC schemes and stages of CH recovery are reviewed. By devising new TC techniques, CHs recovery strategies that partially or wholly repair LSCHs and increase the coverage of WSNs are presented such that a global pattern emerges as a result of nodes' local interactions.

In this study, we propose **(1)** CH detection and boundary node (B-node) selection algorithms, which B-nodes around the damaged area self-select solely based on available 1-hop information extracted from their simple geometrical and statistical features. **(2)** A constraint node movement algorithm based on the idea of virtual chord (v-chords) formed by B-nodes and their neighbours to partially repair CHs. By changing each B-node's v-chord, its movement and connectivity to the rest of network can be controlled in a distributed manner. **(3)** Fuzzy node relocation models based on force-based movement algorithms are suitable to consider the uncertainty governed by nodes' distributed and local interactions and the indefinite choices of movements. **(4)** A model of cooperative CHs recovery in which nodes move towards damaged areas in the form of disjoint spanned trees, which is inspired by nature. Based on nodes' local interactions with their neighbours and their distances to CHs, a set of disjoint trees around the CH spans. **(5)** A hybrid CH recovery strategy that combines sensing power control and physical node relocation using a game theoretic approach for mobile WSNs. **(6)** A sink-based CH recovery via node relocation where moving nodes consider the status of sink nodes.

The proposed node relocation algorithm aims to reduce the distances of moving nodes to the deployed sink nodes while repairing the CHs. The results show that proposed distributed algorithms **(1)-(6)** either outperform or match their counterparts within acceptable ranges.

The significances of proposed algorithms are as follow: Although they are mainly designed base on the available 1-hop knowledge and local interactions of (autonomous) nodes, they result in global behaviours. They can be implemented in harsh and hostile environments in the absence of centralised operators. They are suitable for time-sensitive applications and scenarios with the security concerns that limit the amount of information exchange between nodes. The burden of decision making is spread among nodes.

Acknowledgments

First, I would like to express my deepest appreciations to my supervisor, Dr. Mehran Abolhasan who helped me in my research and who has always been supportive and very patient through my studies despite all the difficulties. I would like to thank my co-supervisor, Dr. Daniel Franklin who gave me valuable feedback and comments during my research. I would also like to thank my previous supervisor Prof. Farzad Safaei from University of Wollongong, Australia for all his feedbacks and continuous supervision even after i transferred to University of Technology, Sydney. I am very grateful for the unique opportunity to work with him. I would like express my gratitude to my alternative supervisor, Prof. Robin Braun for all his kindness and help. I would like to thank Dr. Stephen Smith from Macquarie University for his valuable time and feedback on reading my work and accepting to review the drafts version of my thesis.

I would like to thank my beloved parents, Mohammad and Shahla, for their unlimited support during my studies. Without them it was not possible at all to pass through the hard times. I really appreciate their sacrifice and support for me every single day of my life. I would like to thank my brother and my best friend, Dr. Pedram Rafiei from University of Saskatchewan, Canada who always helped me any possible ways he could from the long distance.

I would like to thanks people who I co-authored a number of papers for the duration of my studies. Special Thanks to Dr. Yashar Maali from University of Technology, Sydney for his help. I also thank my colleagues especially Dr. Abdullah Alsabbagh for his time and creating enjoyable and cooperative environment for me. I would like to express my special thanks to Dr. Wei Ni from Commonwealth Scientific and Industrial Research Organisation (CSIRO) for his invaluable feedback and comments on my work. It was my pleasure to work with him. I would like to thank my former colleague Dr. Banafsheh Lashkari, from Shiraz University for her comments and feedback at the time of preparing the thesis' draft.

I am in debt to anonymous reviewers of my publications for giving feedback and comments which paved the way for new ideas in my research. I would also like to express my appreciation for Australian Research Council (ARC) discovery research grant No. DP0879507 to support my studies and ease the financial burden.

I would like to express my gratitude to Mr. Amir Hesami, Dr. Mohammad Namazi, Dr. Amirreza Niktash, Dr.Reza Memary, Dr. Alireza Banani, Dr. Alireza Mohammadi, Dr. Mehdi Farrokhrooz and Dr. Mostafa Azizpour among many of my friends for their kind hospitality and support.

I would like to express my sincere appreciation for Ms. Phyllis Agius and Mr. Craig Shuard for all their help and advices. I would like to express my gratitude to Ms. Eryani Tjondrowalujo and Ms. Grandia Agathon for their kindness and help with the thesis submission process.

I would like to thank my thesis examiners for their time and for their valuable comments and feedback.

Last but not least, I would like to dedicate my thesis to all the courageous, brave

people, and the soldiers of my country which have sacrificed their lives and health to protect my country, my homeland against enemies and made a secure and safe place to grow and prosper. I salute and pray for their souls and respectable families who have suffered drastically from losing their loved ones.

To my beloved and very dear parents, my true friends Mohammad, and Shahla which have supported me in all aspects and were for me every single moment.

Contents

1	Introduction	1
1.1	Objectives of the Thesis	5
1.2	Thesis Organisation	6
1.3	Summary of Contributions and Publications	10
1.3.1	Contributions not covered in thesis	12
2	Related Work	13
2.1	Wireless Sensor Networks	14
2.1.1	Distributed WSNs	16
2.1.2	Mobile WSNs	16
2.1.3	Coverage and Connectivity	18
2.2	Effect of Mobility	24
2.2.1	Mobility Classification	24
2.3	Effect of Localisation	28
2.4	Network Resiliency	28
2.4.1	Resiliency in Graphs and Nature	34
2.4.2	Resiliency in WSNs	36
2.5	Topology Control Schemes	39
2.5.1	Deployment and Redeployment	42
2.5.2	Node Clustering	46
2.5.3	Routing and Node Discovery	47
2.5.4	Redundancy and Node Power Adjustment	48
2.5.5	Node Scheduling Sleep Cycle Management	50
2.5.6	Node Relocation	51
2.5.7	Hybrid Schemes	60
2.6	Network Events and Faults	62
2.6.1	Events and Faults	62
2.6.2	Fault Management Techniques	64
2.6.3	Network Failures	70

2.7	Network Recovery	79
2.7.1	Recovery Stages	80
2.7.2	Coverage Hole Recovery	82
2.7.3	Resilience Factors in WSNs	97
2.8	Cooperation and Emergence	99
2.8.1	Complex Systems	99
2.8.2	Autonomy and Multi-Agent Systems in WSNs	100
2.8.3	Emergent Cooperation and Collective Behaviour	101
2.9	Conclusion	104
3	Coverage Hole Detection	106
3.1	Introduction	106
3.2	Method and Assumptions	107
3.2.1	Nodes and Deployment Area	107
3.2.2	Coverage Hole	109
3.2.3	Nodes Classification	110
3.2.4	Node Selection Algorithms	113
3.3	Performance Evaluation	118
3.3.1	Performance Metrics	118
3.3.2	Results	119
3.4	Conclusion	122
4	Coverage Hole Partial Recovery by Nodes' Constrained and Autonomous Movements Using Virtual α-chords	123
4.1	Method and Assumptions	124
4.1.1	Sensor Node and Coverage Hole Model	124
4.1.2	Nodes Classification	124
4.1.3	Local Communications Protocol	125
4.1.4	Selection Algorithms	127
4.1.5	Movement Algorithms	127
4.2	Performance Evaluation	131
4.2.1	Performance Metrics	132
4.2.2	Results	132
4.3	Conclusion	137
5	Fuzzy Node Relocation Models	138
5.1	Introduction	138
5.2	Method and Assumption	139
5.2.1	Nodes and Deployment Area	139
5.2.2	Boundary Conditions	139
5.2.3	Fuzzy Logic Parameters	140

5.3	Fuzzy Logic Relocation Models	142
5.3.1	Expert Knowledge Fuzzy Relocation Model	142
5.3.2	Tuned Parameter Fuzzy Relocation Model	144
5.3.3	Iteratively Tuned Parameter Fuzzy Relocation Model	148
5.4	Performance Evaluation	151
5.4.1	Performance Metrics	151
5.4.2	Results	152
5.5	Conclusion	165
6	Cooperative Recovery of Coverage Holes in WSNs via Disjoint Spanning Trees	166
6.1	Introduction	166
6.2	Method and Assumptions	171
6.2.1	Sensor Nodes	171
6.2.2	Coverage Hole	172
6.2.3	Node Types	172
6.2.4	Voronoi Cells	173
6.2.5	Boundary Conditions	174
6.2.6	Disjoint Spanned Tree	175
6.3	Performance Evaluation	185
6.3.1	Performance Metrics	185
6.3.2	Results	186
6.4	Conclusion	215
7	Distributed Hybrid Recovery of Coverage Hole	217
7.1	Introduction	217
7.2	Method and Assumptions	219
7.2.1	Game Theory in Brief	219
7.2.2	Sensor Nodes	221
7.2.3	Coverage Holes	222
7.2.4	Node Types	222
7.2.5	Proposed Hybrid Recovery Algorithm	222
7.2.6	Coverage Problem Formulation	223
7.2.7	Distributed Payoff-based learning algorithm	227
7.3	Performance Evaluations	231
7.3.1	Performance Metrics	231
7.3.2	Results	232
7.4	Conclusion	242
8	Sink-Based Recovery Model	243
8.1	Introduction	243

8.2	Methods and Assumptions	245
8.2.1	Sensor Nodes and Area of Deployment	245
8.2.2	Coverage Holes and Node Types	245
8.2.3	Nodes' Communications Protocol	247
8.2.4	Node Movement Decision	248
8.2.5	Effect of Sink Node	249
8.2.6	Movement Toward CHs	251
8.2.7	Proposed Movement Model	252
8.2.8	Condition at Border of Deployment area	255
8.3	Performance Evaluation	255
8.3.1	Performance Metrics	255
8.3.2	Benchmark Movement Algorithms	257
8.3.3	Results	257
8.4	Conclusion	264
9	Concluding Remarks	266
9.1	Conclusions	266
9.2	Future Research Suggestions	271
	Bibliography	279
A	Boundary Node Selection Algorithms	303
A.1	Introduction	303
A.2	Method and Assumptions	304
A.3	Performance Evaluation	310
A.4	Conclusion	314
B	Performance of DSSA for Large Scale CH	315
B.1	Introduction	315
B.2	Method and Assumptions	316
B.3	Performance Evaluation	319
B.4	Conclusion	319
C	Fuzzy Logic Movement Model Figures	320

List of Figures

2.1	Stack Diagram of Sections	14
2.2	Coverage Categories	21
2.3	Mobility Categories	25
2.4	Topology Control Scheme Categories	40
2.5	Node Failure Categories in WSNs	41
2.6	Network Failure Management and Recovery Stages	70
2.7	Categories of Coverage Holes	77
2.8	Network Resilience Factors and Indicators	97
3.1	Coverage Hole	108
3.2	Node Types	109
4.1	Coverage Hole and Node Types	125
4.2	B-Node, its real, virtual neighbors and virtual chord	126
4.3	Chord movement algorithm ($R_c=15$, $N=600$, $\beta=0$)	128
4.4	Percentage of Recovery	133
4.5	Percentage of Connectivity	134
4.6	Average Movement	134
5.1	Memberships	143
5.2	Fuzzy Node Movement Algorithms	144
5.3	Radial and Angular Membership function	146
5.4	Fuzzy Node Movement Algorithms, Figure 5.2	147
5.5	Radial and Angular Membership functions of Node after 50 Iterations	148
5.6	Fuzzy Node Movement Algorithms, Figure 5.4	150
5.7	Percentage of 1-Coverage (100%) for different boundary conditions with angular force strategy A_1	154
5.8	Uniformity for different boundary conditions with angular force strategy A_1	155

5.9	Average movement for different boundary conditions with angular force strategy A_1	156
5.10	Performance Comparison of Relocation Algorithm for globally and locally ($R_{zone} = f1, 2, 4g \cdot R_c$) Tuned fuzzy parameters	159
5.11	Performance of Different Movement Strategies with Boundary condition B_2 and Angular Force Strategy A_1	160
5.12	Comparison of Performances of Movement Algorithms for $\omega_1 = 0, \omega_2 = 0, \omega_3 = 1$	162
5.13	Comparison of Performances of Movement Algorithms (FRM) for $(\omega_1, \omega_2, \omega_3) = (1, 0, 0), (0, 1, 0), (0, 0, 1)$	163
6.1	Coverage Hole and Types of Nodes	168
6.2	Specimen of lichtenberg Figure obtained by using a spherical electrode [365]	169
6.3	Disjoint Spanned Trees (DS-Tree) around CH	170
6.4	Block Diagram of the CH boundary detection algorithm and Node types	174
6.5	Block Diagram for Recovery Stages of CH	176
6.6	Block Diagram of the Root Node Selection Algorithm	179
6.7	Block Diagram of the Disjoint Spanned Trees Algorithm	183
6.8	Percentage of 1-Coverage of Relocation Algs. for $N=500$, and radii of $R_{Hole} = (40, 50, 60, 70)m$	187
6.9	Uniformity of Relocation Algs. for $N=500$, and radii of $R_{Hole} = (40, 50, 60, 70)m$	188
6.10	Average Movement of Relocation Algs. for $N=500$, and radii of $R_{Hole} = (40, 50, 60, 70)m$	191
6.11	Efficiency of Movement of Relocation Algs. for $N=500$, and radii of $R_{Hole} = (40, 50, 60, 70)m$	192
6.12	Percentage of 1-Coverage of Relocation Algs. $N=500$, $R_{Hole}=50$ and Different participating Nodes	199
6.13	Percentage of 1-Coverage of Relocation Algs. $N=500$, $R_{Hole}=50$ and Different participating Nodes	200
6.14	Uniformity of Relocation Algs. $N=500$, $R_{Hole}=50$ and Different participating Nodes	202
6.14	Uniformity of Relocation Algs. $N=500$, $R_{Hole}=50$ and Different participating Nodes (cont'd)	203
6.15	Average Movement of Relocation Algs. $N=500$, $R_{Hole}=50$ and Different participating Nodes	205
6.15	Average Movement of Relocation Algs. $N=500$, $R_{Hole}=50$ and Different participating Nodes (cont'd)	206

6.16	Percentage of 1-Coverage of Relocation Algs. for $N=500$, $R_{Hole}=50$ for N_p =Closest $X\%$ of U-nodes	207
6.17	Percentage of 1-Coverage of Relocation for Algs. $N=500$, $R_{Hole}=50$, N_p =Level L of DS-Trees of U-nodes	209
6.18	Uniformity of Relocation Algs. for $N=500$, $R_{Hole}=50$ for N_p =Closest $X\%$ of U-nodes	211
6.19	Uniformity of Relocation Algs. for $N=500$, $R_{Hole}=50$, N_p =Level L of DS-Trees of U-nodes	212
6.20	Average Movement of Relocation Algs. for $N=500$, $R_{Hole}=50$ for N_p =Closest $X\%$ of U-nodes	213
6.21	Average Movement of Relocation Algs. for $N=500$, $R_{Hole}=50$, N_p =Level L of DS-Trees of U-nodes	214
7.1	Profit of sensor i	225
7.2	k-Coverage of Network $N = 400$ Nodes and Random Consecutive Damage Events (Coverage Holes)	235
7.2	k-Coverage of Network $N = 400$ Nodes and Random Consecutive Damage Events (Coverage Holes) (Cont'd.)	236
7.3	Algorithms' Percentage of Coverage vs Processing Time, Iterations $N = 400$ Nodes	237
7.4	Percentage of Avg . Coverage vs Number of Nodes	238
7.5	Algorithm Consumed Energy vs. Number of Nodes	238
7.6	Algorithms' Percentage of Coverage/Energy vs Time, $N = 400$ Nodes	239
8.1	Relocation of Boundary nodes in Sink-based CH Recovery Model	244
8.2	Coverage Hole, Node Types $N = 500$ nodes, and $R_c = 15 m$	246
8.3	Boundary Node and its Undamaged and Damaged Neighbour Nodes	247
8.4	Circle Inversion	250
8.5	Sparsity of Network	260
8.6	Percentage of Coverage	261
8.7	Avg Distances CHs' Boundary Nodes to Sink Node	261
8.8	Max Distances CHs' Boundary Nodes to Sink Node	262
8.9	Min Distances CHs' Boundary Nodes to Sink Node	262
A.1	Coverage Hole	304
A.2	QB (0.5) OB-Node Selection Algorithm applied on B-nodes	308
A.3	Cosine Law Boundary Min Distance, Selection Algorithm	308
A.4	5 Distribution of Angles (histogram) OB-nodes at (x_{hole}, y_{hole})	311
A.5	Average distances from damage area of BNS-algorithms	312
A.6	Number of Selected B-nodes of BNS-algorithms	313
A.7	Perc-k-RSC of BNS-algorithms	314

B.1	Network Hole and Node Types	316
B.2	Network Deployment Stages in the Recovery, Performed by DSSA on Boundary/Undamaged Nodes	317
B.3	Network Coverage Stages in the Recovery, Performed by DSSA on Boundary/Undamaged Nodes	318
C.1	Percentage of 1-Coverage (100%) for different boundary conditions with angular force strategy A_2	321
C.2	Uniformity for different boundary conditions with angular force strategy A_2	322
C.3	Average movement for different boundary conditions with angular force strategy A_2	323

List of Tables

2.1	Some definitions of Resilience and Network Resiliency in the literature.	35
2.2	Some definitions of the complex systems' and agents' collected behaviour and Cooperation in the literature.	105
3.1	Stage-wise B-node Selection	117
3.2	BNS-Algorithms percentage of AVD,PCov improvement over MB (Number of SB-nodes 20-100)	120
3.3	AVD and PCov of BNS-algorithms	121
4.1	Performances of Movement Algorithms	135
5.1	Fuzzy Rules	141
5.2	Membership Functions	145
5.3	Percentage of Improvement over DSSA for 1-Coverage (100%)	157
5.4	Uniformity (Difference with DSSA)	157
5.5	Average Movement (Difference with DSSA)	157
6.1	Percentage of 1-Coverage of Relocation Algs. Different CH Radius $R_{Hole}=(40, 50, 60, 70)$ m , $N=500, 1000$ Nodes	194
6.2	Uniformity of Relocation Algs. Different CH Radius $R_{Hole}=(40, 50, 60, 70)$ m and $N=500, N=1000$ Nodes	195
6.3	Average Efficiency of Movement of Relocation Algs. Different CH Radius $R_{Hole}=(40, 50, 60, 70)$ m $N=500, N=1000$ Nodes	196
6.4	Number of Participating Nodes for $N=500$ Nodes and Coverage Hole Radius, $R_{Hole}=50$ m	201
7.1	Description of Variables	228
7.2	Value of Variables	232
7.3	Value of Stopping Criteria for $N = 200, 400$ Deployed Nodes	237

7.4 Avg. Coverage and Energy vs. Number of Deployed Nodes	240
7.5 Coverage and Energy vs. Number of Deployed Nodes	241
8.1 Sparsity of Network with Sink Nodes located at (100,100) and 5 Consecutive CHs	259
8.2 Percentage of Coverage of Network, with Sink Nodes located at (100,100) and 5 Consecutive CHs	260
8.3 Distances to Sink Nodes located at (100,100) and 5 Consecutive CHs	263

List of Algorithms

3.1	Distance-based Boundary Node Selection Algorithms	111
3.2	Degree-based Boundary Node Selection Algorithms	112
3.3	VD Boundary Node Selection	115
3.4	VA Boundary Node Selection	116
4.1	Nodes' neighbors selection Algorithms	129
4.2	Formation of Chord Algorithm	130
5.1	Iteratively tuned fuzzy logic relocation model	149
6.1	DS-Tree Movement Algorithm	177
6.2	Root Nodes Selection Algorithm	178
6.3	Disjoint Spanned Trees Algorithm	180
6.4	Chain Node Movement DS-Tree Alg.	184
7.1	Proposed Algorithm	229
A.1	Boundary Selection Algorithms	306
A.2	Boundary Node Selection Algorithms (Alg. A.1 Contd.)	307

List of Abbreviations

ADL	Absolute Degree Loss
AVD	Average Distance from Damaged Area
aM-CSSCMM	M-CSSCMM based on the amplitude
B-B cell	B-Node Voronoi Cell Neighbour with B-node Voronoi Cell
B-D cell	B-Node Voronoi Cell Neighbour with D-node Voronoi Cell
B-node	Boundary Node
BNS-Algorithm	Boundary Node Selection Algorithms
CA	Cellular Automata
CCP	coverage configuration protocol
CH	Coverage Hole
CHR	Coverage Hole Recovery
CHD	Coverage Hole Detour
CI	Confidence Interval
CLAvgB	Cosine Law Average Boundary
CLMinB	Cosine Law Min Boundary
CM	Center of Mass
C-Mobility	Controlled Mobility
CNF-algorithm	Closer Nodes First Algorithm
CP	Candidate Parent

CSSCMM	Combined SS and CM Movement
D-area	Damaged Area
D-event	Damage Event
D-node	Damaged Node
DHSCL	Distributed Homogeneous Synchronous Coverage Learning Algorithm
dM-CSSCMM	M-CSSCMM based on the angle
DN-node(s)	Damaged Neighbour Node(s)
DSN	Distributed Sensor Network
DSSA	Distributed Self-Spreading Algorithm
DS-Tree	Disjoint Spanned Tree
DUCM-Algs.	DN-nodes and UN-Nodes' Centre of Mass Algorithm
EC	Emergent Cooperation
ECE	Efficiency of Consumed Energy
FAM	Fuzzy Angular Movement
FARM	FAM then FRM
FRM	Fuzzy Radial Movement
FRAM	FRM then FAM
FRNAM	FRM and FAM
GPS	Global Positioning System
HBD	Hole Boundary Detection
LSCH	Large Scale Coverage Hole
k-RSC	k-redundant sensing coverage
MANETS	Mobile ad hoc networks
MAS	Multi-Agent System
MaxD-algorithm	Maximum Distance Algorithm
MinD-algorithm	Minimum Distance Algorithm

MB-node(s)	Margin of Boundary node(s)
M-CSSCMM	Modified CSSCMM
MWSNs	Mobile WSNs
N-node	Normal Node
NE	Nash equilibrium
Perc-k-RSC	percentages of k-redundant sensing coverage
PCov	Percentage of Coverage
PP	Potential Parent
PSO	Particle Swarm Optimization
QoS	Quality of Service
RBN	Random Boundary node
RDL	Relative Degree Loss
R_c	Transmission Range
R_s	Sensing Range
RE	Residual Energy
ROI	Region Of Interest
QB	Quantile-based (comparative) Boundary
S-Coverage	Spatial Coverage
SB-Node	Selected Boundary Node
SS	Simple Sink
SSCH	Small Scale Coverage Hole
SSM	Simple Sink Movement
T-Coverage	Temporal Coverage
TC	Topology Control
TS	Takagi and Sugeno
UAV	Unmanned aerial vehicle
U-node	Undamaged Node

UDG	Unit Disk Graph
U-Mobility	Uncontrolled Mobility
UN-node	Undamaged Neighbour Node
V-chord	Virtual Chord
V-Hole	Virtual Hole
V-node	Virtual Node
VA-Algorithm	Voronoi Area Algorithm
VarD-Algorithm	Variance of Distance Algorithm
VD-Algorithm	Voronoi Distance Algorithm
WQB	Weighted quantile-based Boundary
WSN	Wireless Sensor Network